



TESTING SERVICES, INC.
817 SHOWALTER AVE. • P.O. BOX 2041
DALTON, GEORGIA 30722-2041
PHONE: (706) 226-1400 • FAX: (706) 226-6118

CLIENT:	Global Syn-Turf	REPORT NUMBER:	57084
	2482 Technology Drive	LAB TEST NUMBER:	2506-5378
	Hayward, CA 94545	DATE:	January 15, 2013

Test Material:

Turf Identification	Infill
GST Emerald	1.0 lbs/ft ² 20-40 Silica Sand

SUBJECT: Testing Services Inc was instructed by the client to determine the flammability of finished synthetic turf when exposed to an ignition source under controlled laboratory conditions.

TEST METHOD: ASTM D-2859: *Standard Test Method for Flammability of Finished Textile Floor Covering Materials*

Code of Federal Regulations: 16 CFR 1631 (FF2-70) < 6ft & 24 ft²

Code of Federal Regulations: 16 CFR 1630 (FF1-70) > 6ft & 24 ft²

TEST SCOPE: This test method is part of the standards for the surface flammability of carpets and rugs of the U.S. Consumer Product Safety Commission. The acceptance criteria of this standard calls for the charred portion of at least seven out of eight individual specimens not extend to within 1" of the steel frame placed on top of the sample when exposed to a centrally placed methenamine pill tablet.

TEST DATA:


Specimen Number	Un-charred Area
01	>2.0"
02	>2.0"
03	>2.0"
04	>1.0"
05	>3.0"
06	>1.0"
07	>2.0"
08	>2.0"

Note: The above listed infill system was installed prior to testing.

TEST SUMMARY:

Pass	Failure	Status
8	0	Passes

Approved By:


Erle Miles Jr. VP
Testing Services Inc.



TESTING SERVICES, INC.
817 SHOWALTER AVE. • P.O. BOX 2041
DALTON, GEORGIA 30722-2041
PHONE: (706) 226-1400 • FAX: (706) 226-6118

CLIENT:	Global Syn-Turf	REPORT NUMBER:	56981
	2482 Technology Drive	LAB TEST NUMBER:	2503-5273
	Hayward, CA 94545	DATE:	January 3, 2013

Test Material:

Turf Identification	Infill
GST Stemgrass	1.0 lbs/ft ² 20-40 Silica Sand

SUBJECT:

Testing Services Inc was instructed by the client to determine the flammability of finished synthetic turf when exposed to an ignition source under controlled laboratory conditions.

TEST METHOD:

ASTM D-2859: Standard Test Method for Flammability of Finished Textile Floor Covering Materials

Code of Federal Regulations: 16 CFR 1631 (FF2-70) < 6ft & 24 ft²

Code of Federal Regulations: 16 CFR 1630 (FF1-70) > 6ft & 24 ft²

TEST SCOPE:

This test method is part of the standards for the surface flammability of carpets and rugs of the U.S. Consumer Product Safety Commission. The acceptance criteria of this standard calls for the charred portion of at least seven out of eight individual specimens not extend to within 1" of the steel frame placed on top of the sample when exposed to a centrally placed methenamine pill tablet.

TEST DATA:


Specimen Number	Un-charred Area
01	>2.0"
02	>2.0"
03	>1.0"
04	>1.0"
05	>2.0"
06	>2.0"
07	>2.0"
08	>1.0"

Note: The above listed infill system was installed prior to testing.

TEST SUMMARY:

Pass	Failure	Status
8	0	Passes

Approved By:


Erle Miles Jr. VP
Testing Services Inc.